



कार्यालय वन मण्डल अधिकारी सीधी, वनमण्डल सीधी (म.प्र.)

पता :- कोतवाली रोड सीधी (म.प्र.) पिन 486661 दूरभाष नंबर 07822-252235 E-mail :- dfot.sdh@mp.gov.in

क्र./ भण्डार/निविदा/ 4577

सीधी, दिनांक : 12 / 05 / 2026

Corrigendum / संशोधन सूचना

ई-निविदा क्रमांक : 2026_MPFD_502922_1


SUPPLY FENCING MATERIAL (PRCC POLE, RCC POLE, BARBED WIRE AND CHAINLINK FENCING (AS PER ATTACHED TENDER DOCUMENT)

विषय: BOQ फ़ाइल में संशोधन

उपरोक्त संदर्भित ई-निविदा के संबंध में समस्त इच्छुक निविदाकारों को सूचित किया जाता है कि निविदा की शर्तों में निम्नानुसार संशोधन / स्पष्टीकरण जारी किया जाता है —

निविदा पोर्टल पर तकनीकी त्रुटि के कारण पूर्व में गलत (अन्य निविदा से संबंधित) BOQ फ़ाइल संलग्न हो गई थी। उक्त त्रुटि को सुधारते हुए अब सही एवं निविदा-संबंधित BOQ फ़ाइल संलग्न की जा रही है। सभी निविदाकारों को निर्देशित किया जाता है कि वे केवल इस संशोधित BOQ फ़ाइल को ही मान्य मानें। पूर्व में संलग्न BOQ फ़ाइल अमान्य होगी और उस पर आधारित कोई भी गणना/प्रस्ताव स्वीकार नहीं किया जाएगा। निविदा की अन्य शर्तें एवं नियम यथावत रहेंगे। यह संशोधन आदेश निविदा दस्तावेज़ का अभिन्न अंग होगा।

संलग्न - BOQ फ़ाइल |



वन मण्डल अधिकारी
वन मण्डल सीधी

क्र./ भण्डार / निविदा / 4578

प्रतिलिप :

सीधी, दिनांक : 12 / 05 / 2026

1. क्रय समिति, वन मण्डल सीधी ओर की ओर सूचनार्थ एवं आवश्यक कार्यवाही हेतु अग्रेषित।


वन मण्डल अधिकारी
वन मण्डल सीधी

Item Rate BoQ

Tender Inviting Authority: DIVISIONAL FOREST OFFICER-SIDHI MP

Name of Work: सामग्री आपूर्ति निविदा आमंत्रण वर्ष २०२५-२६

Contract No: Note- BASIC RATE In Figures To be entered by the Bidder BOQ file-(fill basic rate including GST, Transportation charge etc.)

Name of the Bidder/
Bidding Firm /
Company:

PRICE SCHEDULE

(This BOQ template must not be modified/replaced by the bidder and the same should be uploaded after filling the relevant columns, else the bidder is liable to be rejected for this tender. Bidders are allowed to enter the Bidder Name and Values only)

NUMBER #	TEXT #	NUMBER #	TEXT #	NUMBER #	NUMBER #	TEXT #
Sl. No.	Item Description	Quantity	Units	BASIC RATE In Figures To be entered by the Bidder BOQ file-(fill basic rate including GST, Transportation charge etc.) Rs. P	TOTAL AMOUNT with all tax and gst	TOTAL AMOUNT In Words
1	2	4	5	13	54	55
1.01	PRCC Fencing Pole: Pre Stressed RCC FENCING POLES- Type- Straight length 2.00 meter, Dimensions top to bottom 10x10 cm square, Cement Concrete mix- Concrete mix shall be conforming to grade M-15 IS 4996:1984 Reinforcement - There shall be 4 Nos. for Vertical reinforcement of high tensile steel wire of 4mm dia. Holes 6 Nos. bottom hole should be provided 50 cm above the bottom of the poles. The Central distance between the top and bottom holes shall be equally divided for remaining hole J Hook shall be of 6mm dia MS Bar with proper threads at one end and nut and washer for tightening purpose. These J bolts shall be pass through the holes of Poles. Standard-Conforming to IS 4996:1984 With Up to date amendments.	1.000	प्रति नग		0.000	INR Zero Only
1.02	RCC FENCING POLES Type - Straight Length - 2.00 Meter Dimensions - Bottem 10x10 cm square, Top 8x8 cm square. Cement Concrete Mix -Cement, Sand and metal ratio 1:2:4 with 12.5 nominal size coarse aggregate. Sand used should be free from clay and salt. Concrete mix shall be conforming to grade M-15 of IS:456:2000 Reinforcement - 4 round vertical bars of 6 mm diameter, 11 no. of stirrups of 6 mm diameter round MS bars 20 cm center to center. Hooks - 5 no., bottom hook should be provided 60 cm above the bottom of the poles, second at 82.5 cm, third hook 112.5 cm. fourth hook at 150cm, top and fifth hook at 195 cm from bottom. Manufacturing - In order to ensure desired compressive strength, RCC fencing poles should be compacted with the help of platform vibrators, Surface should be uniform and free from voids. The concrete cover over the reinforcement should not be less than 1.5 cm. Standard Conforming to IS 4996:1984 with up to date amendments.	1.000	प्रति नग		0.000	INR Zero Only
1.03	बारबेड वायर (बंटीलातार / BARBED WIRE) GALVANIZED STEEL BARBED WIRE - Line Wire - Galvanised steel wire of 2.5 mm diameter Point Wire - Galvanised steel wire of 2.5 mm diameter Barbs - Distance between two barbs 75mm, the barbs shall have four points and shall be formed by twisting two point wire each two turns, tightly around both the line wire making altogether four complete turns. Standard - Conforming to IS 278:2009	1.000	प्रति किलो ग्राम		0.000	INR Zero Only
1.04	Galvanized steel chain link fence Galvanized steel chain/link fence fabric- size 100x100 mm, Dia 4.00 mm Mesh wire and 4.50 mm Dia Line wire 2 nos. Upto 2mtr. Width and 3 Nos. Above 2mtr. Standard - Conforming to IS 2721:2003	1.000	प्रति वर्ग मीटर		0.000	INR Zero Only
Total In Figures					0.000	INR Zero Only
Quoted Rate in Words					INR Zero Only	