

BHARAT RATAN DR. BHUPEN HAZARIKA MUSEUM AT GUWAHATI, ASSAM						
SPECIFICATIONS OF FLOORING FOR DIFFERENT AREAS OF THE BUILDING						
GROUND FLOOR						
S.No.	SPECIFIC SPACE	INTERNAL WALL	FLOORING	CEILING	DOOR	REMARKS
1	Reception/Entrance Lobby	Glazed Door/ Window	Laminated wooden flooring	Aluminum baffle in wooden finish	12mm thick toughen glass door/ window	
2	Exhibition Space	Vitrified tile skirting + fine flakes texture paint	Two Different shades of Terrazo flooring (Soft colors)	POP False ceiling as per design	12mm thick toughen glass door	Magnetic Tracks + Access Panel
3	Cafeteria	100mm high vitrified tile skirting + texture paint finish upto bottom of false ceiling	900 X900 Full body vitrified tiles flooring / epoxy flooring	aluminum baffle in wooden finish		
4	Kitchen + Service Area	300 x 450 Ceramic tiles	full body vitrified Antiskid floor tiles(Matt Finish)	Enamel Paint	35mm thick laminated Flush Door + wood Door Frame	
5	Toilets	dado in 300 x 600 ceramic wall tiles up to false ceiling + cubical partition will be in HPL (marino or equivalent)	600 x 600 full body vitrified Antiskid floor tiles(Matt Finish)	perforated aluminium ceiling	35mm thick core veneered finsh Flush Door + Hard Door Frame	Same Shade tiles as used in Dining area + Steel grey / coffee brown counter top + Ash grey

NOTE :Recessed POP False ceiling as per design out Sprinkler

FIRST FLOOR						
S.No.	SPECIFIC SPACE	INTERNAL WALL	FLOORING	CEILING	DOOR	REMARKS
1	Central Passage	Glazed Door/ Window	Laminated wooden flooring	Aluminum baffle in wooden finish	12mm thick toughen glass door/ window	MS and Glass Railing
2	EXHIBITION SPACE	Vitrified tile skirting + fine flakes texture paint	Two Different shades of Terrazo flooring (Soft colors)	POP False ceiling as per design	12mm thick toughen glass door	
3	Hologram Theatre	As per specialised vendor				
4	Artifacts Exhibition space	vitrified / epoxy skirting +design in texture paint	900 X900 Full body vitrified tiles flooring	Aluminum baffle in wooden finish	35mm thick laminated Flush Door + wood Door Frame	Similar Terazzo Texrure
5	Toilets	dado in 300 x 600 ceramic wall tiles up to false ceiling + cubical partition will be in HPL (marino or equivalent)	600 x 600 full body vitrified Antiskid floor tiles(Matt Finish)	perforated aluminium ceiling	35mm thick core veneered finsh Flush Door + Hard Door Frame	Same Shade tiles as used in Dining area + Steel grey / coffee brown counter top + Ash grey

SECOND FLOOR						
S.No.	SPECIFIC SPACE	INTERNAL WALL	FLOORING	CEILING	DOOR	REMARKS
1	EXHIBITION SPACE	Vitrified tile skirting + fine flakes texture paint	Terrazo flooring	POP False ceiling as per design	12mm thick toughen glass door	Two Different shades of Terrazo flooring (Soft colors) + Magnetic Tracks + Access Panel + Bum Rail

THIRD FLOOR						
S.No.	SPECIFIC SPACE	INTERNAL WALL	FLOORING	CEILING	DOOR	REMARKS
1	Temporary Exhibition Gallery	Vitrified tile skirting + fine flakes texture paint	Terrazo flooring	POP False ceiling as per design	12mm thick toughen glass door	Two Different shades of Terrazo flooring (Soft colors) + Magnetic Tracks + Access Panel + Bum Rail
2	Admin Office	Acrylic emulsion paint (VOC)	600 x 600 full body vitrified floor tiles	Perforated metal tile	35mm thick laminated Flush Door + anodized Door Frame	
3	Store	Enamel Paint + 100 mm kota stone skirting	550 x 550 kota stone floor	plaster +Cement based putty	35mm thick laminated Flush Door + anodized Door Frame	

SPECIFICATIONS OF FLOORING FOR DIFFERENT AREAS OF THE BUILDING, BHUPEN HAZARIKA MUSEUM, GUWAHATI, ASSAM						
COMMON SPACES						
1	Lift (Passenger)	Router cut SS Steel and lacquered glass panels (60 % + 40%)	18 mm thick Granite floor	Wooden ceiling +3mm SS Plate+ Router cut ss sheet	12mm thick toughen glass door 2 hour fire rated glass door	
2	Fire Staircase	Terrazo Skirting + Texture paint	18 mm thick Granite floor	Acrylic emulsion paint (VOC)	fire rated door	
3	Staircase	Terrazo Skirting + Texture paint	In-situ Terrazo flooring			Uniformly Inclined Skirting +Tension wire Railing with Bamboo Partial Cladding
4	Services	Enamel PAINT + 100 mm kota stone skirting	550 x 550 kota stone floor	plaster +Cement based putty	fire rated door	

S.No.	SPECIFIC SPACE	MATERIAL SPECIFICATIONS
1	Landscape	White Leaf Grass
2	Outer Facade	Texture Exterior Paint + Water Proof Coating
3	Outer Facade Louvers	MS Rectangular Channels + Waterproof Paint Coating + MS Plate
4	Central Plaza	Coonor Stone + Granite (Flamed) + Dark grey paint