

**NIT Schedule of Item for Annual repair work of Govt.
Non Residential Building Biaora Section Sub Division Rajgarh**

PAC Rs. In lakh 5.00

S.N.	SOR item No.	Item	Qnt	Rate	Unit	Amount
1	2	3	4	5	6	7
1	14.1	Repairs to plaster of thickness 12mm to 20mm in patches of area 2.5 sq. metres and under including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete including disposal of rubbish to the dumping ground within 50metres lead :With cement mortar 1:4 (1 cement : 4 sand)	200	180	Sqm	36000
2	14.2	Fixing chowkhats in existing opening including embedding chowkhats in floors or walls cutting masonry for holdfasts, embedding hold fasts in cement concrete blocks of size 15 x 10 x 10 cm with cement concrete 1:3:6 (1 cement : 3 sand : 6 graded stone aggregate 20 mm nominal size), painting two coats of approved wood preservative to sides of chowkhats and making good the damages to walls and floors as required complete including disposal of rubbish to the dumping ground within 50 meters lead :				
	14.2.1	Door chowkhats	2	544	Each	1088
	14.2.2	Window chowkhats	3	325	Each	975
3	14.3	Fixing chowkhat in existing opening in brick / RCC wall with dash fasteners/ chemical fastener of appropriate size (3nos on each vertical member of door chowkhat and 2 nos. on each vertical member of window chowkhats) including cost of dash fasteners/ chemical fastener.	4	146	Each	584
4	14.4	Making the opening in brick masonry including dismantling in floor or walls by cutting masonry and making good the damages to walls, flooring and jambs complete to match existing surface i/c disposal of mulba/ rubbish as directed by Engineer-in-charge.For door/ window/ clerestory window.	2	323	Sqm	646
5	14.5.1 & 14.5.2	Renewing glass panes, with putty and nails				
		Float glass panes of thickness 4 mm	6	679	Sqm	4074
		Float glass panes of thickness 5.5 mm	6	759	Sqm	4554
6	14.8.1 & 14.8.2	Supplying and fixing new wooden fillets wherever necessary:				
		2nd class teak wood fillets	8	30	Mt	240
		Haldu/Bija/Kail wood fillets.	8	26	Mt	208

S.N.	SOR item No.	Item	Qty	Rate	Unit	Amount
1	2	3	4	5	6	7
7	14.16	Raking out joints in lime or cement mortar and preparing the surface for re-pointing or replastering including disposal of rubbish to the dumping ground within 50 metres lead.	10	17	Sqm	170
8	14.21.1.1	Providing and fixing 25 mm thick shutters for cup board etc. : Panelled or panelled and glazed shutters : Superior class teak wood including nickel plated bright finished M.S. piano hinges with necessary screws.	10	3794	Sqm	37940
9	13.27.1	G.I. chicken mesh as per ISI specification and in the required width with 50mm long Bombay nails before plastering up to 10 meter height.	20	62	Sqm	1240
10	9.35.1.1	providing and fixing wooden moulded beading to door and window frames with iron screws ,plugs and priming coat on unexposed surface etc. Complete. 2 nd class teak wood 50x12 mm.	40	102	meter	4080
11	18.6.1.1 & 18.6.1.3	Providing and fixing chlorinated polyvinyl chloride (CPVC) pipes having thermal stability for hot and cold water supply including all CPVC plain and brass threaded fittings i/c fixing the pipe with clamps at 1.00 m spacing concealed work including cutting chases and making good the walls etc.				
		15 mm nominal outer dia .pipes	60	129	meter	7740
		25 mm	60	177	meter	10620
12	18.29.1	Providing and fixing brass bib cock of approved quality: 15 mm nominal bore	20	306	Each	6120
13	17.73.2	Providing and fixing CP brass towel rail of approved quality and make.450x20mm.	6	836	Each	5016
14	13.36	Providing and fixing broken glass in cement mortar 1.3 including cost of mortar. Over compound walls.	10	139	Sqm	1390
15	17.58.1	Providing and fixing unplasticised rigid PVC soil and waste pipes conforming to IS: 13592 type B including jointing with seal ring conforming to IS: 5382 leaving 10 mm gap for thermal expansion single socketed pipes for working pressure of 4 kg /sqm.75 mm diameter (minimum wall thickness 3.2mm)	40	136	meter	5440

S.N.	SOR item No.	Item	Qty	Rate	Unit	Amount
1	2	3	4	5	6	7
16	11.82.1.1	Providing and laying digital print random design(PGVT)/(GVT) vitrified tiles in different sizes with water absorption less than 0.05% and conforming to IS:15622 of approved make in all colours& shades, 1st quality / premium in skirting, riser laid on 12mm thick cement mortar 1:3 including grouting the joints with white cement and matching pigments etc. complete For floor glossy/ rustic /stain/matt finished laid on 20mm thick cement mortar 1:4 (1 cement:4sand) Size 600X600 mm thickness 9-10 mm	120	1140	Sqm	136800
17	18.44.1	Providing and fixing PTMT bib cock of approved quality and colour. 15mm nominal bore, 86mm long. Weighing not less than 88 gms.	5	173	Each	865
18	15.12	Dismantling stone slab flooring laid in cement mortar including stacking of serviceable material and disposal of unserviceable material within 50 metres lead.	120	64	Sqm	7680
19	15.6.2	Dismantling brick work manually /by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metreslead as per direction of engineer –in-charge. In lime mortar.	4	202	sqm	808
20	15.14.1	Dismantling doors ,windows and clerestory windows (steel or wood) shutter including chowkhats, architrave, holdfasts etc. Complete and stacking within 50 metres lead .	40	85	Each	3400
21	6.6.1	Brick work with well brunt open bhatta, bricks, crushing strength not less than 25kg / cm2 and water absorption not more than 20% in superstructure above plinth level and up to floor two level i/c curing etc complete. Cement mortar 1:4 (1 cement : 4 sand)	8	4541	Cum	36328
22	13.1	12 mm cement plaster of mix . 1:6	120	160	Sqm	19200
23	13.6	18mm cement plaster in two coats under layer 12mm thick cement plaster 1:5 and a top layer 6mm thick cement plaster 1:3 finished rough with sponge.	30	220	Sqm	6600
24	10.5.2	(25) Providing and fixing 1mm thick M.S. sheet door with frame of 40x40x5 mm angle iron and 3mm M.S.gussct plates at the junctions and corners all necessary fittings complete, including applying a priming coat of approved steel primer.Using flats 30x6mm for diagonal braccs and cntral cross piece.	10	2474	Sqm	24740

S.N.	SOR item No.	Item	Qty	Rate	Unit	Amount
1	2	3	4	5	6	7
25	10.22.2	Steel work welded in built up section / framed work including cutting hoisting fixing in position and applying a priming coat of approved steel primer using structural steel etc. As required . In gratings, frames, guard bar , ladder , railings brackets , gates and similar works.	250	105	Kg.	26250
26	5.16.7	Reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding including cost of binding wire all wastages and overlaps, couplers (overlaps shall be provided as per requirement of IS 13920 for ductile detailing IS 456 RCC Design & SP 34 Reinforcement detailing) etc. complete .(Note:- 1. Spacer bars (chairs) shall be paid separately as shown in the drawing and as per direction of engineer in charge. 2. No extra payment shall be done for overlaps and/or couplers. 3. Couplers shall be conforming to IS code on “Reinforcement Couplers for Mechanical Splices of Bars for Concrete Reinforcement -Thermo-Mechanically Treated bars.FE 500 or more conforming to IS 1786	200	77	Kg.	15400
27	5.9	Centering and shuttering including strutting, propping etc. and removal of form for: 5.9.1 foundations footings bases of columns etc. For concrete up plinth level.	10	190.60	Sqm	1906
		5.9.6 Columns, P i l l a r s , Piers, Abutments, Posts and Struts.	21	471.2	Sqm	9895
		5.9.2.1 walls (any thickness) including attached pilasters buttresses plinth beams and string courses etc. Up to plinth level.	20	219	Sqm	4380
		5.9.3 Suspended floors , roofs, landings, balconies, and access platform .	3	439	Sqm	1317
28	5.1	Providing and laying in position specified grade of reinforced cement concrete (with 20mm nominal size graded stone aggregate) excluding the cost of centering shuttering finishing and reinforcement –all work up plinth level. M 20-grade concrete.	4	6153	Cum	24612

S.N.	SOR item No.	Item	Qty	Rate	Unit	Amount
1	2	3	4	5	6	7
29	5.2.1	Reinforced cement concrete work (with 20 mm nominal size graded stone aggregate) in walls (any thickness), including attached pilasters, buttresses, plinth and string courses, fillets, columns, pillars, posts and struts etc. above plinth level and upto floor two level excluding cost of centering, shuttering, finishing and reinforcement: M-20 Grade Concrete	6	6231	Cum	37386
30	11.36	Kota stone slab flooring over 20 mm (average) thick base laid over and jointed with grey cement slurry mixed with pigment to match the shade of the slab including rubbing and mirror polishing complete with base of cement mortar 1 : 4 (1 cement : 4 sand) 25 mm thick.(Area of slab to be over 0.25 sqm) Note: - Deduction shall be made for not mirror polishing according to item no 11.43 s	12	1174	Sqm	14088

Total
Say Rs. In Lakh

499780
5.00

Sub Engineer
P.W.D. (B&R)
Rajgarh

Sub Divisional Officer
P.W.D. (B&R) Sub Division
Rajgarh

Executive Engineer
P.W.D. (B&R) Division
Rajgarh