

**NIT Schedule for White wash/ Colour Wash, painting in Residential Building
Rajgarh Under Sub Division Rajjgarh**

PAC in Lakh 10.00

S.No.	Description of item	Qty.	Rate	Unit	Amount
1	2	3	4	5	6
	SOR Item No. 14.30				
1	Removing dry or oil bound distemper, water proofing cement paint and the like by scrapping, sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete.	5600	sqm	6.00	33600
	SOR Item No. 14.49.1				
2	Finishing walls with water proofing cement paint of required shade : Old work (one or more coats applied @ 2.20 kg/10 sqm) over priming coat of primer applied @ 0.80 liters/10 sqm complete including cost of Priming coat.	3250	sqm	42.00	136500
	SOR Item No. 13.41				
3	Providing and applying white cement based putty of average thickness 1 mm, of approved brand over the plastered wall surface to prepare the surface even and smooth i/c all cost of material, labour and scaffold etc in all position complete. Note : Putty shall be applied only on the internal walls, for application on the exterior walls prior permission of APD/Chief Engineer will be required.	1800	sqm	74.00	133200
	SOR Item No. 13.54.3				
4	Finishing walls by any mechanical or manual means with Deluxe Multi surface paint system for interiors and exteriors using Primer as per manufacturers specifications :	2250	sqm	81.00	182250
	SOR Item No. 14.27				
5	Removing white or colour wash by scrapping and sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete.	2800	sqm	5.00	14000
	SOR Item No. 14.53.1				
6	Finishing walls with DeluxeMulti surface paint system for interiors and exteriors using Primer as per manufacturersspecifications : One or more coats applied on walls @ 0.85 ltr/10 sqm.	2100	sqm	58.00	121800

S.No.	Description of item	Qty.	Rate	Unit	Amount
1	2	3	4	5	6
	SOR Item No. 13.42				
7	Providing and applying special putty in two coats based materials varnish, Belgium chalk, turpentine oil, white paint, safeda including sand papering for making the surface smooth for applying any or vinyl paints including all cost of material and labouretc complete.	1350	sqm	52.00	70200
	SOR Item No. 14.37				
8	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade: One or more coats on old work.	2100	sqm	35.00	73500
	SOR Item No. 13.45				
9	Distempering with 1st quality acrylic distemper (ready mixed) having VOC (Volatile Organic Compound) content less than 50 grams/ltr of approved manufacturer, of required shade and colour complete, as per manufacturer's specification. Two or more coat on new work.	1200	sqm	75.00	90000
	SOR Item No. 14.29				
10	Distempering with oil bound washable distemper of approved brand and manufacture to give an even shade: Old work (one or more coats).	1575	sqm	21.00	33075
	SOR Item No. 13.67.3				
11	Applying priming coats with primer of approved brand and manufacture, having low VOC (Volatile Organic Compound) content. With water thinnable cement primer on wall surface having VOC content less than 50 grams/litre.	4650	sqm	24.00	111600

999725

10.00

Sub Engineer
P.W.D. (B&R)
Rajgarh

Sub Divisional Officer
P.W.D. (B&R) Sub Division
Rajgarh

Executive Engineer
P.W.D. (B&R) Division
Rajgarh