

NIT Schedule for White wash/ Colour Wash, painting in Non Residential Building Rajgarh Under Sub Division Rajgarh

PAC in Lakh

5.00

S.No.	Description of item	Qty.	Rate	Unit	Amount
1	2	3	4	5	6
	SOR Item No. 14.30				
1	Removing dry or oil bound distemper, water proofing cement paint and the like by scrapping, sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete.	2100	sqm	6.00	12600
	SOR Item No. 14.49.1				
2	Finishing walls with water proofing cement paint of required shade : Old work (one or more coats applied @ 2.20 kg/10 sqm) over priming coat of primer applied @ 0.80 liters/10 sqm complete including cost of Priming coat.	1400	sqm	42.00	58800
	SOR Item No. 13.41				
3	Providing and applying white cement based putty of average thickness 1 mm, of approved brand over the plastered wall surface to prepare the surface even and smooth i/c all cost of material, labour and scaffold etc in all position complete. Note : Putty shall be applied only on the internal walls, for application on the exterior walls prior permission of APD/Chief Engineer will be required.	1300	sqm	74.00	96200
	SOR Item No. 13.54.3				
4	Finishing walls by any mechanical or manual means with Deluxe Multi surface paint system for interiors and exteriors using Primer as per manufacturers specifications :	900	sqm	81.00	72900
	SOR Item No. 14.27				
5	Removing white or colour wash by scrapping and sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete.	2500	sqm	5.00	12500
	SOR Item No. 14.53.1				
6	Finishing walls with DeluxeMulti surface paint system for interiors and exteriors using Primer as per manufacturers specifications : One or more coats applied on walls @ 0.85 ltr/10 sqm.	1500	sqm	58.00	87000
	SOR Item No. 13.42				

S.No.	Description of item	Qty.	Rate	Unit	Amount
1	2	3	4	5	6
7	Providing and applying special putty in two coats based materials varnish, Belgium chalk, turpentine oil, white paint, safeda including sand papering for making the surface smooth for applying any or vinyl paints including all cost of material and labouretc complete.	1300	sqm	52.00	67600
	SOR Item No. 14.37				
8	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade: One or more coats on old work.	850	sqm	35.00	29750
	SOR Item No. 13.45				
9	Distempering with 1st quality acrylic distemper (ready mixed) having VOC (Volatile Organic Compound) content less than 50 grams/ltr of approved manufacturer, of required shade and colour complete, as per manufacturer's specification. Two or more coat on new work.	250	sqm	75.00	18750
	SOR Item No. 14.29				
10	Distempering with oil bound washable distemper of approved brand and manufacture to give an even shade: Old work (one or more coats).	600	sqm	21.00	12600
	SOR Item No. 13.67.3				
11	Applying priming coats with primer of approved brand and manufacture, having low VOC (Volatile Organic Compound) content. With water thinnable cement primer on wall surface having VOC content less than 50 grams/litre.	1300	sqm	24.00	31200

499900

5.00

Sub Engineer
P.W.D. (B&R)
Rajgarh

Sub Divisional Officer
P.W.D. (B&R) Sub Division
Rajgarh

Executive Engineer
P.W.D. (B&R) Division
Rajgarh